

**Solis**

**THE TOUGHEST  
PERFORMER  
FOR YOUR FIELD**

**H26**



**THERMO DYNAMICS  
BONNET & TWIN  
PROJECTOR LAMPS**

**MID & REAR  
PTO**

**SEPARATE PEDAL  
FOR FORWARD  
& REVERSE**

**CRUISE  
CONTROL**

**QUICK ATTACH  
MOWER**



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

**STRATEGIC  
COLLABORATION  
WITH  
YANMAR**

THE TOUGHEST  
PERFORMER  
« FOR YOUR FIELD »

H26

Solis



FEATURES	H26
<b>ENGINE</b>	
Engine Type	Mitsubishi 3-Cylinder Diesel Motor
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry with clogging sensor
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the engine compartment, downward discharge
<b>TRANSMISSION</b>	
Drive	4 WD
Clutch	Wet type clutch for PTO
Gearbox	Hydrostatic
Front Axle	4WD
Transmission	HST (2-Stufen Hydrostat)
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	21.03@2660
Minimum Speed (Km/Hr)	3.18 at low idle 900 erpm, 8.83@rated erpm
<b>BRAKES</b>	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
<b>Differential Lock</b>	
Differential Lock	Yes, Foot Operated
<b>PTO</b>	
PTO (rpm)	Mid PTO- 2100 RPM, Rear 540
PTO (actuation)	Electro hydraulic operated/mechanical selector lever
<b>STEERING</b>	
Steering	Power steering
<b>ELECTRICAL</b>	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
<b>HYDRAULICS</b>	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional hydraulic circuit	1 DW
Hydraulic Lifting Capacity	600 Kg
Lift Rods	Standard
Litre per Minute(LPM)	16.5

FEATURES	H26		
<b>SAFETY SWITCH</b>			
PTO Safety	Standard		
Neutral Safety Switch	Standard		
Clutch Safety Switch	Standard		
<b>CAPACITY (LTRS)(+/-5%)</b>			
Fuel Tank (Lit)	22		
<b>TURNING RADIUS</b>			
Without brakes (m) as per standard tyres	3.05 (RHS), 2.62 (LHS)		
<b>TYRE</b>			
Front	6.00-12		
Rear	8.30-20		
<b>DIMENSION &amp; WEIGHT(+/-5%)</b>			
Weight (Kg)	1235		
Wheel Base (mm)	1570		
Total Length (mm)	2895		
Total Width (mm)	1215 (max)-1050 (min)		
Height (mm) Up to ROPS	2325		
Min Ground Clearance (mm)	240		
Front Track (mm)	885		
Rear Track (mm)	960		
<b>OTHERS</b>			
Fuel Indicator Gauge	Standard		
Front Tow Hook	Standard		
Front & Rear Weights with std. Ballast	Front weights - 2 x 15 Kg		
Trailer Hitch	Towbar, Drawbar (optional)		
ROPS	Yes		
<b>OPTIONAL FEATURES</b>			
Cabin Option	Yes		
<b>Tyres</b>			
Radial Agri: Front   Rear	Turf: Front   Rear	Ind: Front   Rear	GALAXY PRO
6.5/80-12 280/70 R18	25x8.50-14 13.60-16	23x8.50-12 33x15.50-16.5	F - 220/55R12 R - 280/70R16
Front loader	YES optional		

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax: +91- 01882-522222 | Email: info@solis.com | URL: www.solistractors.com/www.solisworld.com